Yuasa Fiche de données techniques

Yuasa YBX3057 - Batteries SMF YBX3000

Performance

Tension	12V
Capacité (20 heures)	45Ah
Performances en démarrage à froid (EN1)	400A



Dimensions

Longueur	238mm
Largeur	129mm
Hauteur	225mm

Poids & Mesures

Poids moyen avec acide	12.4kg

Caractéristiques du bac

Type de bac	JIS B24
Schéma de montage	1
Système de fixation	N
Indicateur de l'état de charge	✔
Poignées	✔
Sortie(s) d'aération	✔
Type de couvercle	Double capot (anti-écoulement et sans entretien)


Technologie

Dispositif stop-flamme	✔
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✔
Taux de charge recommandé	3A
Performance Marking	W3-C2-V2-E1

Type de bornes


T1/T3

Standard DIN Post



Remove T1 adapter for T3

Schéma de montage des éléments



Système de fixation de la batterie



Date de publication: 29/03/2024 - E&OE

Yuasa Technical Data Sheet

Yuasa YBX3057 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	400A



Dimensions

Length	238mm
Width	129mm
Height	225mm

Weights & Measures

Mean Weight with Acid	12.4kg

Container Features


Case Type	JIS B24
Cell Layout	1
Hold Down	N
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	3A
Performance Marking	W3-C2-V2-E1

Terminal Type

T1/T3
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE