



## Yuasa Fiche de données techniques

### Yuasa YBX3027 - Batteries SMF YBX3000

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Tension	12V
Capacité (20 heures)	62Ah
Performances en démarrage à froid (EN1)	550A

#### Dimensions

Longueur	243mm
Largeur	175mm
Hauteur	190mm



#### Poids & Mesures

Poids moyen avec acide	16kg
------------------------	------

#### Caractéristiques du bac

Type de bac	L2 DIN
Système de fixation	B13B14
Indicateur de l'état de charge	✓
Poignées	✓
Sortie(s) d'aération	✓
Type de couvercle	Double capot (anti-écoulement et sans entretien)


#### Technologie

Dispositif stop-flamme	✓
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✓
Taux de charge recommandé	4A
Performance Marking	W3-C2-V2-E1


#### Type de bornes

##### T1

Standard DIN Post




#### Schéma de montage des éléments



#### Système de fixation de la batterie

B3/B4 (B3 with Hold-Down adaptor)



Date de publication: 15/04/2021 - E&OE



## Yuasa Technical Data Sheet

### Yuasa YBX3027 - YBX3000 SMF Batteries

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Voltage	12V
Capacity (20-hour)	62Ah
Cold Cranking Amps (EN1)	550A

#### Dimensions

Length	243mm
Width	175mm
Height	190mm

#### Weights & Measures

Mean Weight with Acid	16kg
-----------------------	------



#### Container Features

Case Type	L2 DIN
Hold Down	B13B14
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


#### Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca
VDA Roll Over Test	PE
Recommended Charge Rate	✓
Performance Marking	4A
	W3-C2-V2-E1

#### Terminal Type

##### T1


Standard DIN Post



Positive Terminal


Negative Terminal

#### Cell Assembly Layout



#### Battery Hold-down

B3/B4 (B3 with Hold-Down adaptor)



Data Sheet generated on 15/04/2021 - E&OE