



Yuasa Fiche de données techniques

Yuasa YBX3077 - Batteries SMF YBX3000

Performance

Tension	12V
Capacité (20 heures)	45Ah
Performances en démarrage à froid (EN1)	380A

Dimensions

Longueur	207mm
Largeur	175mm
Hauteur	190mm



Poids & Mesures

Poids moyen avec acide	12.7kg
------------------------	--------

Caractéristiques du bac

Type de bac	L1 DIN
Schéma de montage	1
Système de fixation	B3
Indicateur de l'état de charge	✓
Poignées	✓
Sortie(s) d'aération	✓
Type de couvercle	Double capot (anti-écoulement et sans entretien)


Technologie

Dispositif stop-flamme	✓
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✓
Taux de charge recommandé	3A
Performance Marking	W3-C2-V2-E1

Type de bornes

T1


Standard DIN Post




Positive Terminal

Negative Terminal

Schéma de montage des éléments



Système de fixation de la batterie



Date de publication: 02/12/2023 - E&OE



Yuasa Technical Data Sheet

Yuasa YBX3077 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	380A

Dimensions

Length	207mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	12.7kg
-----------------------	--------



Container Features

Case Type	L1 DIN
Cell Layout	1
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid


Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	3A
Performance Marking	W3-C2-V2-E1

Terminal Type

T1


Standard DIN Post




Positive Terminal

Negative Terminal

Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 02/12/2023 – E&OE