Yuasa Fiche de données techniques

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3202 - Batteries SMF YBX3000

Performance

Tension	12V
Capacité (20 heures)	42Ah
Performances en démarrage à froid (EN1)	390A



Dimensions

Longueur	175mm
Largeur	175mm
Hauteur	190mm

Poids & Mesures

Poids moyen avec acide	10.5kg

Caractéristiques du bac

Type de bac	L0 DIN
Système de fixation	B3
Indicateur de l'état de charge	✔
Poignées	✔
Sortie(s) d'aération	✔
Type de couvercle	Double capot (anti-écoulement et sans entretien)

Technologie

Dispositif stop-flamme	✔
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✔
Taux de charge recommandé	2A
Performance Marking	W4-C2-V3-E1

Type de bornes

T1
Standard DIN Post






Schéma de montage des éléments



Système de fixation de la batterie



Date de publication: 29/03/2024 - E&OE

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3202 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	42Ah
Cold Cranking Amps (EN1)	390A



Dimensions

Length	175mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	10.5kg

Container Features


Case Type	L0 DIN
Hold Down	B3
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	2A
Performance Marking	W4-C2-V3-E1

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE