Yuasa Fiche de données techniques

Yuasa YBX5202 - Batteries SMF YBX5000 Silver Haute Performance

Performance

Tension	12V
Capacité (20 heures)	45Ah
Performances en démarrage à froid (EN1)	440A



Dimensions

Longueur	175mm
Largeur	175mm
Hauteur	190mm

Poids & Mesures

Poids moyen avec acide	10.8kg

Caractéristiques du bac

Type de bac	L0 DIN
Système de fixation	B3
Indicateur de l'état de charge	✔
Poignées	✔
Sortie(s) d'aération	✔
Type de couvercle	Double capot (anti-écoulement et sans entretien)

Technologie

Dispositif stop-flamme	✔
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✔
Taux de charge recommandé	2A
Performance Marking	W4-C2-V3-E1

Type de bornes

T1
Standard DIN Post






Schéma de montage des éléments



Système de fixation de la batterie



Date de publication: 29/03/2024 - E&OE

Yuasa Technical Data Sheet

Yuasa YBX5202 - YBX5000 Silver High Performance SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	440A



Dimensions

Length	175mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	10.8kg

Container Features


Case Type	L0 DIN
Hold Down	B3
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	2A
Performance Marking	W4-C2-V3-E1

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE