



Yuasa Fiche de données techniques

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX7027 - Batteries EFB YBX7000 Start Stop Plus

Performance

Tension	12V
Capacité (20 heures)	65Ah
Performances en démarrage à froid (EN1)	600A

Dimensions

Longueur	242mm
Largeur	175mm
Hauteur	190mm

Poids & Mesures

Poids moyen avec acide	16.6kg
------------------------	--------



Caractéristiques du bac

Type de bac	L2 DIN EFB
Type de bornes	T1
Système de fixation	B3
Indicateur de l'état de charge	✓
Poignées	✓
Sortie(s) d'aération	✓
Type de couvercle	Double capot (anti-écoulement et sans entretien)

Technologie

Dispositif stop-flamme	✓
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✓
Taux de charge recommandé	4A
Performance Marking	W3-C2-V3-M1

Type de bornes

T1

Standard DIN Post





Schéma de montage des éléments



Système de fixation de la batterie

Date de publication: 10/02/2025 - E&OE



Yuasa Technical Data Sheet

Yuasa YBX7027 - YBX7000 EFB Start Stop Plus Batteries

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Performance

Voltage	12V
Capacity (20-hour)	65Ah
Cold Cranking Amps (EN1)	600A

Dimensions

Length	242mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	16.6kg
-----------------------	--------

Container Features

Case Type	L2 DIN EFB
Terminal Type	T1
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W3-C2-V3-M1

Terminal Type

Cell Assembly Layout

Battery Hold-down

Data Sheet generated on 10/02/2025 – E&OE