



## Yuasa Fiche de données techniques

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

### Yuasa YBX7096 - Batteries EFB YBX7000 Start Stop Plus

#### Performance

Tension	12V
Capacité (20 heures)	75Ah
Performances en démarrage à froid (EN1)	700A

#### Dimensions

Longueur	278mm
Largeur	175mm
Hauteur	190mm

#### Poids & Mesures

Poids moyen avec acide	19.3kg
------------------------	--------



#### Caractéristiques du bac

Type de bac	L3 DIN EFB
Système de fixation	B3
Indicateur de l'état de charge	✓
Poignées	✓
Sortie(s) d'aération	✓
Type de couvercle	Double capot (anti-écoulement et sans entretien)


#### Technologie

Dispositif stop-flamme	✓
Technologie	Ca/Ca
Séparateur	PE
Test de retournement VDA	✓
Taux de charge recommandé	4A
Performance Marking	W3-C2-V3-M1


#### Type de bornes

##### T1


Standard DIN Post



#### Schéma de montage des éléments



#### Système de fixation de la batterie



Date de publication: 15/04/2021 - E&OE



## Yuasa Technical Data Sheet

### Yuasa YBX7096 - YBX7000 EFB Start Stop Plus Batteries

\* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

#### Performance

Voltage	12V
Capacity (20-hour)	75Ah
Cold Cranking Amps (EN1)	700A

#### Dimensions

Length	278mm
Width	175mm
Height	190mm

#### Weights & Measures

Mean Weight with Acid	19.3kg
-----------------------	--------

#### Container Features

Case Type	L3 DIN EFB
Hold Down	B3
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

#### Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W3-C2-V3-M1

**Terminal Type**

**Cell Assembly Layout**

**Battery Hold-down**

Data Sheet generated on 15/04/2021 – E&OE